

Technical Data Sheet

Page No. 1

1. Product and Introduction

Product Name	P885
Backing Material	Polyester Y wt
Bonding	Resin over Resin
Mineral Type	Aluminum Oxide (Compact grain($Al_2 O_3$))
Coating State	Semi Closed coat
Manufacturing Width	1360mm

2. Available Grit

Grit	16	24	36	40	50	60	80	100	120	150	180	220
									●		●	
	240	280	320	360	400	500	600	800	1000	1200	1500	2000

◀ Rough(Grinding)

Finishing(Polishing) ▶

- Introductory Remarks ● : Standard Grit △ : Non Standard Grit

3. Advantage

- ◆ Providing uniform scratch pattern.
- ◆ Excellent Long life.
- ◆ High productivity.

4. Operation / Application

- ◆ Automotive
- ◆ Welding seams containers
- ◆ Stainless steel sheets & coils
- ◆ Turbine blade

5. Work pieces

- ◆ Steel(alloyed, non-alloyed).
- ◆ Non-ferrous metals
- ◆ Stainless Steel

6. Available Sander / Grinder

- ◆ Disc
- ◆ Backstand.
- ◆ Wide & Narrow belt
- ◆ Centerless
- ◆ ConveyORIZED through feed belt grinder